

# RC200 P T3

## Single Drum Soil Compactor



**WACKER  
NEUSON**  
*all it takes!*

### Product Highlights

- 3-point articulation for outstanding traction and offroad mobility
- Operating concept Easy Drive
- Electronic machine management
- Excellent view of the machine and the construction site
- High compaction performance thanks to high linear load and big amplitudes



*Picture is for illustration purposes only and may vary from specification sheet designation*

### Clean Compaction Force

The Wacker RC Series Soil Compactors are powerful professionals with great compaction force well suited for today's earthworks.

Production output is high due the 3 point articulation and large departure angles both front & rear and are extremely maneuverable with optimum driving stability.

The Wacker RC Series are fitted with modern low emission Deutz engines with proven technology. The operators station is ergonomically optimised and simple to operate.

In addition to this, these machines have excellent vision of the drum & work environment around the machine. Maintenance is easy with the wide opening engine hood which simplifies access for daily checks and delivers easy access to service points.

Email: [info@conplant.com.au](mailto:info@conplant.com.au)



hire



sales



parts



service

[conplant.com.au](http://conplant.com.au) | 1300 166 166

TECHNICAL DATA	Unit	RC200 P T3
<b>Weights</b>		
Operating weight with cab	kg	20000
Operating weight with ROPS	kg	19780
Operating weight, max.	kg	21730
Axle load, front/rear	kg	12690/7310
French classific., data/class		79,46/VP5
<b>Machine dimensions</b>		
Total length	mm	6210
Total height with cab	mm	3050
Height loading, min.	mm	2350
Wheel base	mm	3165
Total width with cab	mm	2390
Ground clearance, centre	mm	425
Turning radius, inside	mm	4180
Angle of driving slope, front/rear	°	37/27
<b>Drum dimensions</b>		
Drum width, front	mm	2220
Drum diameter, front	mm	1784
Drum thickness, front	mm	35
Drum type, front		Padfoot
Height of the padfeet	mm	100
Padfeet, number		150
<b>Wheel dimensions</b>		
Size of tyres, rear		TR 23.1-26 12 PR
<b>Diesel engine</b>		
Manufacturer		DEUTZ
Version		TCD 2012 L06 2V
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
Emission standard		EU Stage IIIA / EPA Tier 3
<b>Drive</b>		
Speed, working gear	km/h	0-3,8/0-5,3/0-5,9
Speed, transportation gear	km/h	0-11,1
Climbing ability, vibration on/off	%	51/56
<b>Vibration</b>		
Vibration frequency, front, I/II	Hz	27/30
Amplitude, front, I/II	mm	1,93/1,15
Centrifugal force, front, I/II	kN	331/243
<b>Steering</b>		
Oscillation angle +/-	°	10
Steering, type		Articulated steering
<b>Tank capacity/Fill capacity</b>		
Fuel tank, capacity	L	290
<b>Sound level</b>		
Acoustic power LW(A), sticker		105
Acoustic power LW(A), measured		103

Email: [info@conplant.com.au](mailto:info@conplant.com.au)



hire



sales



parts



service

conplant.com.au | 1300 166 166